

Modello	Portata [Kg]	Velocità [m/min.]	Kw	Tiri di catena	A	A1	B	B1	B2	B3	Ø C	C1	C2	C3	D	D1	E	E1	F	Ø G	G1	H	H1	H2	H3	L	M	N	Ø R	S	Ø T	Peso [Kg]
1000WR8	1000	8	2	1	355	90	102	162	375	665	10	12	34	28	280	147	28	30	29	43	32	250	315	345	660	175	160	415	70	390	24	142
1000WR28	1000	2-8	0,5-2	1	355	90	102	162	375	665	10	12	34	28	280	147	28	30	29	43	32	250	315	345	660	175	160	415	70	390	24	144
1500WR4	1500	4	2	1	375	90	102	162	375	665	10	12	34	28	280	147	28	30	29	50	37	250	315	345	660	175	160	415	70	390	24	154
1500WR14	1500	1-4	0,5-2	1	375	90	102	162	375	665	10	12	34	28	280	147	28	30	29	50	37	250	315	345	660	175	160	415	70	390	24	154
2000WR4	2000	4	2	1	375	90	102	162	375	665	10	12	34	28	280	147	28	30	29	50	37	250	315	345	660	175	160	415	70	390	24	154
2000WR14	2000	1-4	0,5-2	1	375	90	102	162	375	665	10	12	34	28	280	147	28	30	29	50	37	250	315	345	660	175	160	415	70	390	24	154

Modello	Portata [Kg]	Velocità [m/min.]	Kw	Tiri di catena	A	A1	B	B1	B2	Ø C	C1	C2	C3	D	D1	E	E1	F	Ø G	G1	H	H1	H2	H3	L	M	N	Ø R	S	Ø T	Peso [Kg]
1000WR12	1000	13,5	3	1	360	90	162	617	905	10	12	34	28	355	147	31	33	29	50	37	200	320	335	655	245	250	450	70	*	24	185
1000WR31	1000	3-12	0,7-3	1	360	90	162	617	905	10	12	34	28	355	147	31	33	29	50	37	200	350	335	685	245	250	450	70	*	24	170
1500WR8	1500	8	3	1	380	90	162	617	905	10	12	34	28	355	147	31	33	29	50	37	200	320	305	625	245	250	450	70	*	24	185
1500WR28	1500	2-8	0,7-3	1	380	90	162	617	905	10	12	34	28	355	147	31	33	29	50	37	200	350	305	655	245	250	450	70	*	24	185
1500WR12	1500	13,5	3	1	380	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	50	37	200	320	335	655	240	255	450	70	*	24	185
1500WR31	1500	3-12	0,7-3	1	380	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	50	37	200	350	335	685	240	255	450	70	*	24	185
2000WR8	2000	8	3	1	380	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	50	37	200	320	335	655	240	255	450	70	*	24	192
2000WR28	2000	2-8	0,7-3	1	380	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	50	37	200	350	335	685	240	255	450	70	*	24	185
2500WR8	2500	8	3	1	420	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	50	37	200	320	335	655	240	255	450	70	*	24	185
2500WR28	2500	2-8	0,8-3,5	1	420	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	50	37	200	350	335	685	240	255	450	70	*	24	185

Modello	Portata [Kg]	Velocità [m/min.]	Kw	Tiri di catena	A	A1	B	B1	B2	Ø C	C1	C2	C3	D	D1	E	E1	F	Ø G	G1	H	H1	H2	H3	L	M	N	Ø R	S	Ø T	Peso [Kg]
3200WR4	3200	4	3	2	490	90	162	617	905	10	12	34	28	355	147	31	33	29	50	37	200	320	305	625	200	295	450	70	*	24	190
3200WR14	3200	1-4	0,7-3	2	490	90	162	617	905	10	12	34	28	355	147	31	33	29	50	37	200	350	305	655	200	295	450	70	*	24	200
4000WR4	4000	4	3	2	515	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	58	42	200	320	335	655	195	300	450	70	*	24	200
4000WR14	4000	1-4	0,7-3	2	515	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	58	42	200	350	335	685	195	300	450	70	*	24	205
5000WR4	5000	4	3	2	515	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	58	42	200	320	335	655	195	300	450	70	*	24	210
5000WR14	5000	1-4	0,8-3,5	2	515	90	162	617	905	11	13,2	37,4	31	355	147	31	33	29	58	42	200	350	335	685	195	300	450	70	*	24	210